

Water Tank Accessories

Genap Tank Ladder

The Genap Tank Ladder is a cost effective and robust system for safe tank inspection. The ladder is suitable for all tank heights up to and including 4.64 metres. The system is equipped with brackets and fixings. The ladder can be self-installed on a new or an existing tank. A cage version is also available for heights above 3.88 metres.



Level Indicator

This simple but very effective system ensures that the water level is always visible, even when the tank is covered. A float in the tank is connected by a cord and pulleys to an indicator in a transparent tube on the outside of the tank. As the water sinks, the indicator sinks with it. If the tank is filled with water, the indicator rises with the water level.

Installation Clamps

For quick and easy installation of the protection fleece and liner, installation clamps can be fitted every 3 to 4 metres. The installation clamps allow one person to install the protection fleece and liner.



Flat Bottom Drain Outlet

With a flat bottom drain outlet the silo can be emptied completely for cleaning or maintenance. The standard lower drain consists of a base plate with a Ø 110 mm pipe attached centrally. Other diameters are available on request.

Water Tank Accessories

Sidewall Outlets up to 200 mm

Sidewall outlets can be placed in the tank as inlet, outlet or overflow. The steel reinforcement plate guarantees the strength and rigidity of the tank panel. The sidewall outlets are available in 90, 150 and 200 mm (galvanised or coated).



Mechanical Sidewall Outlets

Mechanical sidewall outlets are available in 50 (2"), 75 (3") and 100 (4") mm. These glassfibre reinforced nylon outlet sets include the mounting bolts and the reinforcement plate for installation into the tank. The membrane is waterproofed with a rubber seal. The required holes must be drilled on site.

Conical Outlets

Prefabricated conical outlets are used for all inlets and outlets through the base or wall of the tank. This consists of a base plate and a tapered sleeve, which is fixed to the pipe. Available to fit all diameters of pipe the conical outlet is fabricated from the same material as the tank liner. Conical outlets can be prefabricated into the liner at the factory or supplied separately.



Tank Anchor Brackets

If a tank is not buried, it must be firmly anchored so that it is fixed in place and wind resistant. The anchor is fixed to the double bolt row and secured with concrete parabolts. The tank anchor brackets should only be fixed after the tank has been filled.